

**JOURNAL OF CLEAN ENERGY, CIRCULAR  
ECONOMY AND DIGITALISATION**

# **CONFERENCE BOOK OF ABSTRACTS**

26th & 27th September, 2024

# **Journal Of Clean Energy, Circular Economy And Digitalisation**

A Book of Abstracts submitted in the Second Edition of the Africa International Conference on Clean Energy and Energy Storage (AICCEES) 2024.

This Book of Abstracts is compiled by Tovero Energy Ltd. Some of the research abstracts within this book will be considered for publication in a conference proceedings book series by Trans Tech Publications. The publication will be supervised by highly professional members of an International Editorial Board to ensure high-quality publication material.

### **Photocopying**

Single photocopies of single articles may be made for personal use as allowed by national copyright laws. Permission of the organizing institution and publisher is required for all other photocopying including multiple or systematic copying, copying for advertising or promotional purposes or all forms of document delivery.

### **Derivative Works**

Subscribers may reproduce tables of contents or prepare lists of articles including abstracts for internal circulation within their institutions. Permission of the Publisher/ Organizer is required for distribution outside the institution. Resale is not permitted. Permission of the publisher/ Organizer/Author is required for all other derivative works, including compilations and translations.

### **Electronic Storage or Usage**

Permission of the Publisher is required to store or use electronically any material contained in this book including any article or part of an article except as outlined above, no part of this publication may be reproduced, stored in the retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior written permission of the Publisher.

### **Notice**

No responsibility is assumed by the Publisher for any injury and/or damage to persons or property as a matter of products liability, negligence or otherwise, or from any use or operation of any methods, products, instructions, or ideas contained in the material herein.

# PART 1

## HYDROGEN DEVELOPMENT IN NIGERIA

### Design and Analysis of a Supercritical Metal-water Reactor for Hydrogen Gas Production

*IGWE Chijindu Ikechukwu, EZE Paschal Chizuruoke, EZE Miracle Izuchukwu*

*Department of Mechanical Engineering, University of Nigeria Nsukka, Enugu State, Nigeria.*

*chijindu.igwe@unn.edu.ng, pascha.eze.243650@unn.edu.ng, miracle.eze.242916@unn.edu.ng*

**Keywords:** Clean energy; Hydrogen production; Supercritical metal-water reactor; Sustainable technology.

**Abstract:** In this study, a supercritical metal-water reactor for hydrogen production was designed, simulated, and analysed. As the world urgently seeks to transition towards sustainable energy, hydrogen stands out as a pivotal solution in this shift. This project aims to fill knowledge gaps related to the transition to supercritical conditions through comprehensive analysis, thereby contributing to the advancement of clean energy technologies. Mechanical and thermal properties suitable for a supercritical metal-water reactor were modelled and simulated in SolidWorks 2022, utilizing plots and mesh results. The reactor was designed to produce hydrogen gas and metal oxide as by-products, with the hydrogen gas being released through a pressure relief valve. The reactor cylinder, made of Ti-6AL-4V, was found suitable for operation at a constant pressure of 25 MPa and a temperature of 380°C. The reactor wall was observed to buckle at pressures exceeding 27 MPa and temperatures above 144,000°C, which are beyond the design conditions. The elastic limit of the cylinder was determined to be 868 MPa, and its ultimate tensile strength was 1,258 MPa, with fracture occurring at 620 MPa. The average damage percentage was calculated to be 0.001%, and the total lifecycle was estimated at 10,000,000 cycles. The integrity of the reactor designed for supercritical states was found to be structurally sound. Detailed insights into the effects of pressure and temperature on the selected material were analysed, enhancing understanding of the reactor's performance under various conditions.

### A Two-Parameter Computational Thermodynamic Analysis of Hydrogen-Impurity Mixtures in a Repurposed Pipeline

*Yakubu Khartum Abubakar, Binfa Bongfa, Elijah Binfa Bongfa, Muhammed Shaibu, Ahmad Muhammad Zumami*

*Department of Mechanical Engineering, The Federal Polytechnic P.M.B 1037, Idah, Kogi State, Nigeria.*

*Mechanical Engineering Department, Edo State University Uzairue, Edo State, Nigeria.*

*Department of Computer Science, The Federal Polytechnic P.M.B 1037, Idah, Kogi State, Nigeria*

*[ababayaks8069@gmail.com](mailto:ababayaks8069@gmail.com) , [engrbinfabongfa@gmail.com](mailto:engrbinfabongfa@gmail.com), [ebinfabongfa@gmail.com](mailto:ebinfabongfa@gmail.com) ,  
[mdmuhamodu@yahoo.com](mailto:mdmuhamodu@yahoo.com) , [zumamee22@gmail.com](mailto:zumamee22@gmail.com)*

**Keywords:** A two-parameter thermodynamic analysis, hydrogen impurity, repurposed pipeline, Peng-Robinson, hydrogen transportation, non-destructive acoustic emission.

**Abstract:** In this study, a two-parameter computational thermodynamic analysis of a hydrogen-impurity mixture in a repurposed pipeline was performed. The hydrogen purity is a vital aspect of the hydrogen value chain, and it is essential to constantly monitor its purity. We anticipate that refineries will use repurposed pipelines for bulk hydrogen transportation to consumers; however, these pipelines are known to contain impurities. Therefore, there is a need for such an analysis. This study considered two basic thermodynamic parameters: the pressure and gas molar concentration. The Peng–Robinson equation of state was used for the analysis. We implemented octave programming for the Newton–Raphson numerical scheme to obtain the molar volume of the pure hydrogen. Four scenarios were considered: scenario 1 (only hydrogen), scenario 2 (hydrogen mix with H<sub>2</sub>S), and scenario 3 (hydrogen mix with H<sub>2</sub>S, and pentane), and scenario 4 (hydrogen mix with H<sub>2</sub>S, pentane, and propane). We studied the variation in gas pressure with molar concentration. The results showed that, as the number of impurities considered in the analysis increased, the pressure decreased. The pressure of scenario 1 and 2 is approximately Pa, scenario 3 is around Pa, and scenario 4 is around Pa. We can develop a non-destructive acoustic emission hydrogen quality monitoring system by considering how impurities in hydrogen moving through a repurposed pipeline might affect the pressure of the gas moving through the pipeline.

## Development and Evaluation of an Alkaline Electrolyzer for Production of Hydrogen and Electrical Energy in a Fuel Cell

*IGWE Chijindu Ikechukwu, ACHEBE Chinonso Hubert, CHINWEZE Arinze Everest, and CHUKWUNEKE Jeremiah Lekwuwa*

*1Department of Mechanical Engineering, University of Nigeria Nsukka.*

*2Department of Mechanical Engineering, Nnamdi Azikiwe University Awka, Nigeria.*

*[igwechijindu@gmail.com](mailto:igwechijindu@gmail.com), [ch.achebe@unizik.edu.ng](mailto:ch.achebe@unizik.edu.ng), [ae.chinweze@unizik.edu.ng](mailto:ae.chinweze@unizik.edu.ng),  
[jl.chukwuneke@unizik.edu.ng](mailto:jl.chukwuneke@unizik.edu.ng)*

**Keywords:** Alkaline, Electrolysis, Electrolyzer, Hydrogen, Water.

**Abstract:** In this study, a single-cell, zero-gap, unipolar alkaline water electrolyzer which operates on a 30 wt.% KOH electrolyte solution was developed for production of hydrogen. Suitable material properties such as density, toughness, electrical conductivity, and corrosion resistivity were evaluated in Ansys Granta 2019 with the aid of material property charts; and thermal and stress simulations of the modelled components performed using Autodesk Inventor Nastran 2019. A DC power source supplied voltages below 3.0 V across the nickel electrodes, maintaining an operating temperature of 50 °C, and operating pressure at 0.1 MPa. The electrolytic process produced hydrogen and oxygen gases at the electrodes, and the membrane performed the gas separation. Polytetrafluoroethylene plastic was experimentally found to be a superior and more suitable material for the electrolyzer endplates and spacers to polypropylene plastic. Polypropylene nonwoven geotextile fabric was also found to be a low-cost and efficient membrane material, against Zirfon Perl UTP 500 membrane which is an efficient but expensive industrial membrane; polyester geotextile fabric got corroded after about 24 hours of good service. The optimal performance of the electrolyzer cell was obtained at a cell voltage of 2.2 V and a current of 1.30 A, while producing 14 ml of hydrogen gas per minute. This performance gave an electrolysis efficiency of 55.6%, an energy efficiency of 67.3%, and a hydrogen production efficiency of 75.4%. The produced hydrogen and oxygen gases generated electrical energy in a reversible PEM fuel cell device which powered a 0.2 W DC electric motor for a minute.

# Full Spectrum- driven photocatalytic hydrogen production using Fe-doped TiO<sub>2</sub>-MoS<sub>2</sub> Nanocomposites

*Ikechukwu John Oleka, Christogonus Oudnay Akalezi, Solomon Agbo and Emmanuel Emeka Oguzie*

*Department of Electrochemical Technology, Africa Centre of Excellence in Future Energies and Electrochemical Systems, Federal University of Technology, Owerri (ACE-FUELS, FUTO), Nigeria*

*Nigeria Social Insurance Trustfund, Plot 794 corporate head office, Central business district Abuja, Nigeria*

*Forshungszentrum Julich, Germany*

*johnajimo@yahoo.com, akalezichris@gmail.com, slmnagbo@yahoo.com, emeka.oguzie@futo.edu.ng*

**Keywords:** Water splitting, green hydrogen, full spectrum, Fe-doped, TiO<sub>2</sub>-MoS<sub>2</sub>, renewable energy, sustainability.

**Abstract:** The development of efficient and sustainable methods for hydrogen production is crucial for transition to a renewable energy future. In this ongoing research, we will explore the potential of full spectrum driven photocatalytic hydrogen production using Fe-doped TiO<sub>2</sub>-MoS<sub>2</sub>. By leveraging the unique properties of this novel material, we aim to harness energy from the entire solar spectrum to drive hydrogen evolution reactions. Fe-doped TiO<sub>2</sub>-MoS<sub>2</sub> composites have been successfully synthesized using impregnation and solid state approaches respectively. Our preliminary results show that Fe-doped TiO<sub>2</sub>-MoS<sub>2</sub> exhibits enhanced photocatalytic activity and stability under full spectrum illumination, outperforming traditional TiO<sub>2</sub>-based photocatalysts. The incorporation of Fe dopants and MoS<sub>2</sub> is expected to enhance the material's ability to absorb visible and infrared light, increasing hydrogen production rates. This research has significant implications for the development of scalable and efficient photocatalytic hydrogen production systems, offering promising solution for renewable energy storage and conversion. This ongoing study focuses on optimizing material synthesis, characterization, and reactor design to further improve hydrogen yield and overall system efficiency.

# PART 2

## ENERGY EFFICIENCY AND SMART SYSTEM

### Energy efficiency, cost-saving opportunities and nearly zero emissions analysis in the residential sector.

*Omata David Omakoji, Opoku Richard and Zinsou Gil-Christ*

*1, 2, 3. Kwame Nkrumah University of Science and Technology Kumasi, Ghana*

*omatadavid.omakoji@gmail.com, richard.opoku.richardopoku@gmail.com, ygzinsou@gmail.com*

**Keywords:** Energy efficiency, nearly zero emission, cost-saving opportunity, renewable energy, Ghana, Nigeria.

**Abstract:** This study evaluates the energy efficiency, cost-saving opportunities and nearly zero emissions for the residential sectors of Ghana and Nigeria, focusing on three household appliances: fridges, freezers and bulbs. It analyses the integration of renewable energy systems in residential households, comparing energy-efficient and non-energy-efficient scenarios in both countries. The study uses field data, existing data on RETScreen software and analytical methods to examine the energy consumption patterns of key household appliances and their impact on renewable energy system design, cost, and emissions reduction. As for the energy consumption patterns, Ghana showed higher daily usage of household appliances, with longer operational hours for fridges and freezers averaging 20.3 hours/day, while Nigeria had lower daily usage, averaging 11.8 hours/day for similar appliances. For Nigeria, the annual electricity cost in the non-energy-efficient scenario is approximately 109.69 USD, while for energy-efficient households, the cost is reduced to 79.31 USD. In Ghana, non-energy-efficient households spend around 379.97 USD annually, compared to 317.55 USD for energy-efficient homes. The results highlight the significant cost-saving opportunities of adopting energy-efficient technologies. This higher energy demand in Ghana and its higher electricity tariffs lead to greater overall consumption and higher costs. Despite similar appliance wattages, Nigeria's lower tariff results in comparatively lower energy expenses. Using the energy consumption patterns for both countries under the energy-efficient and non-energy-efficient scenarios, system sizing for solar PV and battery storage was conducted to know the economic viability of renewable energy integration through Levelized Cost of Energy (LCOE) and Net Present Value (NPV) assessments. In both scenarios, the payback period for solar PV and battery systems in Nigeria is 22 years, making it not economically viable under current electricity tariffs. In contrast, Ghana shows a payback period of 10.3 years, making solar PV systems financially viable. The RETScreen simulation examined two important scenarios for energy efficiency in Nigeria and Ghana: compact fluorescent lamps (CFLs) as the baseline and LED lighting as a proposed alternative. The results show different GHG (greenhouse gas) reduction equivalences for the number of automobiles that are not driven, the number of individuals who cut their energy use, the number of hectares of forests that absorb GHG, etc. The study's conclusions highlight the significance of energy efficiency in lowering overall energy usage, tariff rates, and expenses associated with solar and battery systems. The results have also provided more insights for both countries to create more comprehensive policies that will encourage adopting energy-efficient practices and make it cheaper for homes to integrate and use renewable energy systems.

## Use of Natural Rocks as Heat-Storage Materials for Food Drying Applications in Sub-Saharan Africa

*Aldé Belgard Tchicaya Loemba, Baraka Kichonge, Thomas Kivevele*

*School of Materials, Energy, Water and Environmental Sciences (MEWES), The Nelson Mandela African  
Institution of Science and Technology (NM-AIST), Tanzania, P.O. Box 447, Arusha – Tanzania*

*Mechanical Engineering Department, Arusha Technical College, P.O. Box 296, Arusha - Tanzania*

*E-mail of corresponding authors: [tchicayaloemba@gmail.com](mailto:tchicayaloemba@gmail.com)*

**Abstract:** The development of affordable solar thermal energy systems for residential and commercial use stands out as one of the best ways to lower the costs of energy consumption and the reliance on solar energy, which is intermittent. Natural rocks are becoming an attractive alternative for thermal energy storage systems in sub-Saharan Africa due to their low cost and accessibility. This study reviews research on natural rocks that are used in Sub-Saharan Africa as heat storage materials for food drying applications. The findings of this study indicate that current research on the combination of drying systems with thermal energy storage systems using natural rocks as storage material focuses on indirect solar dryers (66.67%), mixed mode solar dryers (16.67%), and solar-assisted heat pump dryers (16.67%). These dryers perform admirably, particularly in extreme weather conditions and when there is no sunlight, such as at night. According to the results using a natural rock as storage medium can increase dryer's efficiency up to 17.48%, reduced drying time up to 50%, and extend drying operation from 2 to 4 hours after sunset. Furthermore, the study highlights areas that require additional research, with a particular focus on the characterization of the storage materials used, which is underrepresented in most studies on the continent. In addition, the techno-economic analysis of all these dryers is neglected, making it difficult to assess the economic impacts of these technologies and facilitate their adoption in communities. Exergoeconomic analysis should also be carried out in order to facilitate optimization and understand the actual efficiency of these dryers.

## Performance Analysis of a Photovoltaic System with Thermoelectric Generator and Phase Change Material; An Experimental Approach

*Tobechukwu Okamkpa, Joshua Okechukwu, Divine Mbachu, and Chigbo Mgbemene*

*AEDJAC Lab, University of Nigeria, Nsukka 410001, Enugu, Nigeria*

*Department of Electrical Engineering, Stanford University, Stanford, CA 94305, USA*

*tobechukwu.okamkpa.242531@unn.edu.ng, joshua.okechukwu.247915@unn.edu.ng,  
mbachu@stanford.edu, chigbo.mgbemene@unn.edu.ng*

**Keywords:** Photovoltaic panel, Thermoelectric generator, Phase change material, Experimental analysis, Electrical efficiency.

**Abstract.:** This study explores the integration of thermoelectric generators (TEGs) and phase change materials (PCMs) to enhance the efficiency of photovoltaic (PV) panels in high-temperature conditions. An AP-PM-20 Polycrystalline PV panel, SP-1848-27145 Bismuth Telluride TEG, and paraffin wax PCM in an aluminum container were used. Four configurations were tested: standalone PV, PV-PCM, PV-TEG-PCM, and PV-PCM-TEG, under identical conditions from 10:30 AM to 6:00 PM at 25-minute intervals. Data on PV and TEG voltage, current, and solar irradiance were collected and analyzed.

The results show significant performance improvements: the PV-PCM configuration boosted power output by 68.04%, while PV-PCM-TEG and PV-TEG-PCM configurations improved efficiency by 43.06% and 37.51%, respectively. Efficiency gains relative to the standalone PV system were 33.33% for PV-PCM, 25.76% for PV-PCM-TEG, and 21.21% for PV-TEG-PCM, demonstrating the effectiveness of PCMs and TEGs in enhancing PV performance.

## Energy auditing for University energy management: A tool for enhancing sustainability

*Jeremiah J. John, Adinife P. Azodo, Emmanuel U. Bawa-Boyi, and Francis C Mezue*

*1&3. Department of Pure and Applied Physics Federal University Wukari, Taraba State, Nigeria*

*2. Faculty of Engineering, Federal University Wukari, Taraba State, Nigeria*

*4. Federal Polytechnic Oko, Anambra state, Nigeria*

*johnjeremiahjay@gmail.com, azodopat@gmail.com, boyiemmanuel70@gmail.com, fctmezjob@gmail.com*

**Keywords:** Energy audit, energy monitoring, power consumption, sustainability, efficiency

**Abstract:** Universities are significant energy consumers, and effective energy management is important for sustainability and cost reduction. This article explores the role of energy audits in helping universities improve their energy management and sustainability practices. It analyzes research from 2010 to 2024 to identify various energy auditing techniques, tools, and methodologies used by different institutions. The article demonstrates how diverse auditing approaches can uncover energy inefficiencies and propose practical solutions. Key findings indicate that thorough energy audits are important for promoting sustainability goals through improved energy efficiency and waste reduction. However, universities face challenges in implementing audit recommendations due to infrastructure limitations and technological constraints. The review emphasizes the essential role of energy auditing in enhancing both environmental and economic performance and underscores the importance of ongoing innovation and adaptation in energy auditing practices. In conclusion, the article suggests exploring new technologies and improving auditing techniques to better support sustainability efforts in universities.

## Design and Construction of a smart solar-powered water purification machine

*Ajao, K.R. , Audu, B.H. , Bello, O.M.*

*Department of Mechanical Engineering, University of Ilorin, Ilorin, Nigeria*

**Abstract:** This work presents a solution to the problem of consuming contaminated water in developing nations such as Nigeria, which is blessed with abundant sunlight, by designing and constructing a smart solar-powered water purification machine. The water purification machine employs a six- stage reverse osmosis system incorporating a single-stage RO membrane arrangement. The machine also incorporates sensor and IoT technology, enabling it to self-operate and detect deviations from expected water quality. Water samples from a well and stream in Tanke, Ilorin, Nigeria, were taken. Samples before and after the purification were taken to the Laboratory to test important water quality parameters. Results obtained were within <600ppm for TDS, 6.5 - 8.5 for pH, <5 NTU for turbidity, <600 mg/L for salinity, <500 mg/L for water hardness, <2500  $\mu$ S/cm for EC, >6.5 mg/L for DO,

and 30 - 400 mg/L for total alkalinity, values of which were sourced from WHO and other international bodies that established standards for drinking water quality. The machine's output was determined to be 8 litres/hour, and the ratio of purified water to concentrate was 1:3, signifying a reasonable rate of purified water production.

## PART 3

# MINI-GRIDS AND HYDROPOWER DEVELOPMENT

### Assessing the Viability of Mini-Grids in Rural Electrification: Overcoming Challenges and Exploring Sustainable Business Models

*AYODEJI Stephen Adekanbi*  
14, White Pines Dale, Stocking Avenue, Dublin, Ireland  
*ayodejiadekanbi.s@gmail.com*

**Keywords:** *Mini-grids, rural electrification, Energy access, Solar, Renewable energy*

**Abstract:** In a world where approximately 733 million people lack electricity, the urgency for sustainable energy solutions is paramount. The COVID-19 pandemic has exacerbated the challenge of reaching isolated and vulnerable populations, threatening the goal of universal power access by 2030. Solar mini-grids stand as a beacon of hope, capable of delivering consistent, high-quality electricity to nearly 500 million individuals in regions bereft of power infrastructure. This paper evaluates the economic viability, technological advancements, and challenges hindering the scalability of solar mini-grids. Despite the World Bank's commitment of \$1.4 billion across 30 countries, the current pace suggests that only 44,800 new mini-grids, serving 80 million people, will be established by 2030. The deployment rate of solar mini-grids has accelerated, with installations per country rising from 50 in 2018 to over 150 currently. The cost of electricity from these grids has decreased from \$0.55 per kWh in 2018 to \$0.38 per kWh, enabling the operation of transformative electrical devices. The paper emphasizes the importance of solar mini-grids in reducing CO<sub>2</sub> emissions and proposes actionable recommendations for stakeholders to accelerate deployment. To align with Sustainable Development Goal 7, the paper advocates for the integration of mini-grids into national electrification strategies and innovative financial solutions to mitigate risks. Achieving universal access to power by 2030 will require significant investment and strategic partnerships to bridge the energy divide. Future research directions include exploring new business models to harness the full potential of solar mini-grids and enhance their impact on global electrification efforts. This paper adopted a mixed-methods approach, combining qualitative and quantitative research methods to provide a comprehensive understanding of the potential of mini-grid in rural regions to improve energy access and global electrification efforts. Examining existing rural mini-grid projects through in-depth case studies to understand implementation processes, socio-economic impacts, and challenges faced. Review national and regional policies, regulations, and incentives related to off-grid solar energy deployment to identify gaps and opportunities for improvement. Using economic and business modeling techniques to assess rural mini-grid projects' financial viability and cost-effectiveness, including return on investment and income generation potential.

## Mini-grid Sustainability Framework and its Application to Selected Mini-grids in Kenya

*Mourice Wambua Kausya, Rosebella Nyumba, Elsie Khakasa Onsongo, Daniel Kerr, and Subhes Bhattacharyya*

1. Nuvoni Centre for Innovation Research, Centenary House, Block B 1st Floor Ring Road Westlands Lane, Nairobi, Kenya.
  2. Bergische Universität Wuppertal Gaußstraße 20 42119 Wuppertal, Germany.
  3. Nuvoni Centre for Innovation Research, Centenary House, Block B 1st Floor Ring Road Westlands Lane, Nairobi, Kenya.
  4. De Montfort University, The Gateway Leicester LE1 9BH, United Kingdom.
  5. De Montfort University, The Gateway Leicester LE1 9BH, United Kingdom.
- mkausya@nuvoniresearch.org, nyumba@wiwi.uni-wuppertal.de, eonsongo@nuvoniresearch.org, daniel.william.kerr@gmail.com, subhes.bhattacharyya@dmu.ac.uk*

**Keywords:** sustainability indicators; mini-grids; qualitative data; performance comparison.

**Abstract.** This paper presents an indicator-based framework for the sustainability analysis of mini-grids and applies this to a selection of mini-grids in Kenya. Although various frameworks exist, they have been criticised for lack of attention to long-term perspectives, high data needs, prescriptive nature of the attributes and limited user-friendliness. Considering that data availability is a major concern and that data available is qualitative in nature, this paper proposes a set of indicators and a scoring system that can be used with a broad qualitative understanding of the sustainability attributes of the mini-grids. The paper first presents the framework and the scoring system and applies this to the data gathered from the fieldwork in Kenya. The results indicate that the significant variation in sustainability performance of the mini-grids covered and the performance is relatively poor in social, institutional and environmental dimensions.

## Decarbonisation of the transport sector of Ghana using autogas

*Jeremiah J. John, Adinife P. Azodo, Emmanuel U. Bawa-Boyi, and Francis C Mezue*

- 1&3. Department of Pure and Applied Physics Federal University Wukari, Taraba State, Nigeria
  2. Faculty of Engineering, Federal University Wukari, Taraba State, Nigeria
  4. Federal Polytechnic Oko, Anambra state, Nigeria
- [a\\_johnjeremiahjay@gmail.com](mailto:a_johnjeremiahjay@gmail.com), [b\\_azodopat@gmail.com](mailto:b_azodopat@gmail.com), [c\\_boyiemmanuel70@gmail.com](mailto:c_boyiemmanuel70@gmail.com), [dfctmezjob@gmail.com](mailto:dfctmezjob@gmail.com)*

**Keywords:** CNG, clean mobility, LPG, mathematical model

**Abstract:** Decarbonisation is instrumental in attaining sustainable mobility. To actualize the Ghana Nationally Determined Contribution (NDC) set emission reduction target of 15% relative to BAU scenario by 2030, sustainable transport actions should be encouraged. Thus, promoting the use of LPG and CNG in automobiles is very crucial to ensure efficient and green mobility. Nonetheless, existing policies in Ghana overlook autogas (LPG/CNG) as prospective decarbonizing solution in the transport sector. The study employed survey analysis and analytical modeling approach to elicit the benign effects of autogas in the transport sector.

The ecological, economic and social dimensions of autogas were expatiated to extrapolate effective measures to facilitate the smooth implementation of the technology. Survey was carried out in the central business district of Accra to attain the percentage of autogas and gasoline used by taxis operators for the first time per author's knowledge. From the survey, 14% of taxis were powered with LPG whilst 86% were gasoline, however, the LPG-powered taxis were retrofitted gasoline engine vehicles. The analytical model was based on physics principles involving three resistance forces- aerodynamic, rolling resistance and inertia. CO<sub>2</sub> emission savings of 29% and 18.4% were elicited from the use of CNG and LPG relative to gasoline fuel at the end of the simulation using the ambient conditions in Ghana. Thus, use of autogas will limit global warming impact and aid the country to fulfill its pledged emission target by 2030. The government is entreated to regulate autogas use in the transport sector and increase its patronage by promoting flexible policies like meager custom duty on imported CNG/LPG vehicles as well as tax credits.

## PART 4

# ENERGY STORAGE AND SUSTAINABLE BATTERY MANUFACTURING IN AFRICA

### Comprehensive Investigation Of High-Performance Green-Synthesized NaTi<sub>2</sub>(PO<sub>4</sub>)<sub>3</sub> Nanocomposites For Advanced Electrochemical Energy Storage Applications

*Peredy Khwesa , Edwin U. Onoh, Imosobomeh L. Ikhiya, Chawki Awada, Adil Alshoaibi, Assumpta C. Nwanya,  
Fabian I. Ezema.*

*1Materials Science Program/Department of Chemistry College of Natural and Computational Sciences,  
Addis Ababa University, P.O.Box 1176, Addis Ababa, Ethiopia;*

*Department of Physics and Astronomy, Faculty of Physical Sciences, University of Nigeria, Nsukka, Nigeria*

*Department of Physics, College of Science, King Faisal University, P.O. Box 400, Al Ahsa, 31982, Saudi Arabia*

*Africa Centre of Excellence for Sustainable Power and Energy Development (ACE-SPED), University of  
Nigeria, Nsukka, Nigeria*

**Keywords:** NaTi<sub>2</sub>(PO<sub>4</sub>)<sub>3</sub>/AC nanocomposites, energy storage materials, high-performance electrodes, sustainable energy, next-generation supercapacitor electrodes

**Abstract:** This study investigates a new class of high-performance energy storage electrode materials: NaTi<sub>2</sub>(PO<sub>4</sub>)<sub>3</sub>/AC nanocomposites. Through a comprehensive characterization approach, the study meticulously analyzes the crystal structure, morphology, elemental composition, and electrochemical behavior of these nanocomposites to unlock their potential for energy storage. XRD analysis confirms the successful formation of the composite, revealing distinct peaks characteristic of non-layered activated carbon and crystalline NaTi<sub>2</sub>(PO<sub>4</sub>)<sub>3</sub>. Notably, specific diffraction peaks at 2θ values of 15.3°, 18.3°, 25.3°, 27.6°, 37.8°, 47.3°, and 54.0° corroborate the crystallinity of the NaTi<sub>2</sub>(PO<sub>4</sub>)<sub>3</sub> phase.

Electrochemical characterization conveys that this nanocomposite demonstrates excellent rate capability, retaining 90% of its capacitance even after 3500 cycles, while providing a high 89 Wh kg<sup>-1</sup> density of energy across a remarkable power density of 231 W kg<sup>-1</sup>. Density functional theory (DFT) analysis indicates that the NaTi<sub>2</sub>(PO<sub>4</sub>)<sub>3</sub> nanoparticle is a favorable candidate applied in energy storage owing to its combined mechanical stability and good electronic conductivity, explained by the existence of Ti 3d orbitals in proximity to the Fermi level. Examination of the density of states reveals positive overlap populations between Na-O, Ti-O, and P-O bonds, suggesting strong ionic and covalent bonding, aligning with oxygen 2p and phosphorus 3p orbitals dominating the valence band. In contrast, titanium 3d orbitals contribute to the conduction band, emphasizing robust bonding and good conductivity in the material. These exceptional combined properties position this novel material as a strong candidate for next-generation energy storage applications.

## **Modelling and Optimisation of Solar-PV-Wind-Biomass Energy System with Battery-Hydrogen Energy Storage for Island**

Ekwueme Brendan Ifeanyi, Dr. E. O Diemuodeke, DR. M. M. Ojapah

**Abstract:** This work presents the modelling and optimisation of a hybrid solar PV-Wind-Biomass energy system for Patani island in Delta State. The hybrid system has dual energy storage technologies, namely a battery bank and hydrogen tank. A mathematical model was developed to describe the integrated system and a genetic algorithm was used to formulate the optimisation scheme to balance the energy demand, generation and battery and hydrogen energy storage. Economic models were developed to ascertain the techno-economic feasibility of the hybrid plant. The mathematical model and the optimisation scheme were implemented in high-fidelity software, MATLAB®, and the post-processing of the results was done on the MS Excel® platform. The preliminary results showed that the peak rated power of PV, WT and Biomass required to satisfy the energy demand of Patani island are 15.619 MWh, 0.012MWh and 4794.24MW, respectively. The minimum storage capacity of the battery and hydrogen was estimated at 11.033 MWh and 15.11MWh. The value of 0.45 \$/kWh was obtained for the levelised cost of energy (LCOE), while the loss of load probability of the proposed energy system was estimated at 0.1086. Going forward, sensitivity analysis, validation, simulation, advanced economic analysis and policy pathway will be done to satisfy the objectives of the project.

## **PART 5**

### **ENERGY ACCESS AND ENERGY SUPPLY IN AFRICA**

#### **Hybrid Renewable Energy Systems (HRES) for Nigerian Airports: An Economic Feasibility and Stakeholder Insights Assessment**

*Chidi Cletus Emelu, Johnson Ojiyovwi Okorhi, Roland Uhnmwangho, Ameze Big-Alabo*

*1. Institute of Engineering, Technology and Innovation Management (METI), University of Port Harcourt, Rivers State, Nigeria*

Department of Environmental Management, Dennis Osadebay University, Asaba, Delta State, Nigeria

1. Electrical & Electronic Department, University of Port Harcourt, Rivers State, Nigeria

Corresponding author e-mail: [johnson.okorhi@dou.edu.ng](mailto:johnson.okorhi@dou.edu.ng) Telephone: +234-813-789-1014

Other e-mails: [cletchidi@gmail.com](mailto:cletchidi@gmail.com) and [roland.uhunmwangho@uniport.edu.ng](mailto:roland.uhunmwangho@uniport.edu.ng)

**Keywords:** Economic Viability, Hybrid Renewable Energy Systems (HRES), Levelized Cost of Energy (LCOE), Nigerian Airports, Stakeholder Perceptions

**Abstract:** Due to high electricity costs and unstable national grid power supply, Nigerian airports are challenged with issues that call for the deployment of sustainable and alternative energy sources. The economic viability of hybrid renewable energy systems (HRES) in airports as a sustainable substitute to the national grid is investigated in this study, along with stakeholder perspectives of HRES. Based on a survey conducted among 252 stakeholders in 12 Nigerian airports, the study investigates the implicit high energy costs and varying interest in HRES installations as common problems. Descriptive and inferential statistics were used in the data analysis, and the results showed that although stakeholders are aware of the long-term cost-saving potential of HRES, clear lifecycle cost evaluations are hampered by concerns about early investment costs and a lack of data on the existing HRES installations. Interest in HRES installations is influenced by variables including potential cost savings and instability of the national grid, but then HRES adoptability are likewise influenced by other factors.

## Predictive Modelling for Optimizing Wind Turbine Performance and Structural Health Monitoring: Adapting Turkish SCADA Data for Sub-Saharan Africa

Sikiru Abdulganiyu Siyanbola, Olamide Mercy Oluwatade, and Emmanuel Emeka Okafor

1. Bayero University, Kano, Nigeria

2. University of Ilorin, Nigeria

3. Eurasian National University

[sikirusiyambola@gmail.com](mailto:sikirusiyambola@gmail.com), [mercyolamide5@gmail.com](mailto:mercyolamide5@gmail.com), [okaforemekaemmanuel@gmail.com](mailto:okaforemekaemmanuel@gmail.com)

**Keywords:** Wind Turbine; Predictive Modelling; Structural Health Monitoring; XGBoost Algorithm; Machine Learning.

**Abstract:** This research investigates the application of AI-enhanced structural health monitoring (SHM) systems to predict and optimize the performance and reliability of wind turbines in Sub-Saharan Africa power generation. Supervisory Control and Data Acquisition (SCADA) systems data from a Turkish wind turbine were leveraged to develop a predictive model using the eXtreme gradient boosting (XGBoost) algorithm. Wind speed data from the Turkish wind turbine was substituted with wind speed data of some selected locations in Sub-Saharan Africa (Katsina, Nigeria; Addis Ababa, Ethiopia; Dakar, Senegal; and Cape Town, South Africa). The performance of the models was evaluated using Mean Absolute Percentage Error (MAPE) and the coefficient of determination ( $R^2$ ). The findings show a 0.95% decrease in predicted power output for all the selected locations. The adapted model achieved a MAPE of 1.1% for Addis Ababa, 1.25% for both Cape Town and Katsina, and 1.17% for Dakar, while achieving a high  $R^2$  of 0.96 for all the locations, indicating high predictive accuracy. In scenarios with high wind speed, Dakar has the highest prediction of 3691.09kW, achieving a 1.03% increase compared to Turkey with a predicted power output of 3583.69kW.

Cape Town achieved better prediction accuracy, with a MAPE of 0.78% and  $R^2$  of 0.98, while yielding a power output of 3545.67 kW. This study shows there is vast potential for employing machine learning models in enhancing the operational efficiency of wind turbines. Future study is recommended to incorporate local SCADA data across different wind farms in Sub-Saharan Africa.

## Enhancing Carbon (iv) Oxide Adsorption from Flue Gas Mixture at Elevated Temperature using Composite of Nanoparticles

*Ojong Ojong Elias, Benibo, Preniyobo Diepriye, Abam Fidelis Ibiang, and Dagde Kenneth Kekpugile*

1. Department of Chemical Engineering, Faculty of Engineering and Technology, University of Calabar, Calabar, Cross River State, Nigeria.

2,4. Department of Chemical/Petrochemical Engineering, Faculty of Engineering, Rivers State University, Nkpolu Oroworukwo, Port Harcourt, Rivers State, Nigeria

3. Department of Mechanical Engineering, Faculty of Engineering and Technology, University of Calabar, Calabar, Cross River State, Nigeria

[ojong.ojong@unical.edu.ng](mailto:ojong.ojong@unical.edu.ng); [preni5@yahoo.co.uk](mailto:preni5@yahoo.co.uk); [fidelisabam@unical.edu.ng](mailto:fidelisabam@unical.edu.ng);  
[dagde.kenneth@ust.edu.ng](mailto:dagde.kenneth@ust.edu.ng)

**Keywords:** Adsorption, CO<sub>2</sub>, flue gas mixture, elevated temperature, chitosan/clay nanoparticles.

**Abstract:** Chitosan/clay materials from periwinkle shells and clay soil at a 50:50 ratio was made adsorbent and characterized, used for the adsorption of CO<sub>2</sub> from flue gas at elevated temperatures (500C - 5000C) in a fixed bed column (length 1.5m, and internal diameter 0.02m). Flue gas with composition of Methane (0.003), Ethane (0.002), Hydrogen (0.05), CO<sub>2</sub> (0.15), Water Vapour (0.02), and Nitrogen (0.76), of pressure 49KPa, temperature of 5000C, and flow rate of 75min/L from the exhaust tank; enters the fixed bed column for the adsorption process where the adsorbent is already placed. The results of the characterization of the adsorbent showed that 5.283nm, 2.64nm, 434.7m<sup>2</sup>/g, 704.2m<sup>2</sup>/g, 0.202cc/g, and 56.73% were best the values for the adsorbent' pore width, pore diameter, microspore surface area, pore volume, and porosity, obtained using Dubinin-Raduskevich (DR), density functional theory (DFT), hydraulic diameter (DH), Langmuir, DH, and scanning electron microscope (SEM) analysing techniques respectively. The Fourier transform infrared (FTIR) Spectrum showed the presence of halogen (C-Cl), 20 alcohol (C-O), Nitro (N-O), and amine (N-H) compounds in the nanoparticles, revealing a strong affinity for CO<sub>2</sub> particles in the flue gas. Another analysis showed the presence of elements (Ca, Si, Al, and Sr) in high compositions (0.470, 0.202, 0.186, and 0.092, respectively), revealing that the adsorbent is resistant to high temperatures. X-ray diffraction (XRD) analysis of the adsorbent gave Ca (OH)<sub>2</sub>, CaCO<sub>3</sub>, and TiO<sub>2</sub> with compositions of 0.78, 0.19, and 0.026, respectively which revealed the strong affinity of the adsorbent for CO<sub>2</sub>. The Surface morphology of the adsorbent revealed that the surface was very rough and contains variety of pores or holes with wide capacities, indicating that more CO<sub>2</sub> was captured and accommodated within the surface. Thermal analysis using the Barrett-Joyner-Halenda (BJH) method revealed that the adsorbent could withstand high temperatures up to 9000C, at this temperature, the adsorbent is only about 18% of the amount that enters the fixed-bed column for adsorption, but 100% of it can remain in the process for temperatures ranging from 00C - 3000C. Finally, it was revealed that 95% of CO<sub>2</sub> was adsorbed at the maximum value for the temperature (500C - 3500C), time (0.5 - 5hr), and bed height (1 - 6cm).

# PART 6

## RENEWABLE ENERGY SYSTEM

### Harnessing Geothermal Energy for Decarbonization and Sustainable Agricultural Development using Geotto

*Dominic Kata, Julius Gatune, John Mwit, Lucas Koroso, Victor Kipkorir*

1. Egerton University, P.O. Box 536 20115 Nakuru, Kenya
2. Maastricht School of Management, P.O. Box 616 6200 MD Maastricht, Netherlands
3. Geothermal Development Company, P.O. Box 100746 - 00100, Nairobi Kenya.
4. Eburu Farmers Cooperative, P.O. Box 76, Gilgil, Kenya
5. Moi University, P.O. Box 3900 – 30100, Kesses, Eldoret, Kenya

[katadominic007@gmail.com](mailto:katadominic007@gmail.com), [kariuki@msm.nl](mailto:kariuki@msm.nl), [jmwiti@gdc.co.ke](mailto:jmwiti@gdc.co.ke), [arakaluke@gmail.com](mailto:arakaluke@gmail.com),  
[kipkorirbett69@gmail.com](mailto:kipkorirbett69@gmail.com)

**Keywords:** Geotto, Internet of Things (IoT), HMI, PID, Geothermal Energy, Decarbonization, Artificial Intelligence (AI)

**Abstract:** In this paper, the cases of the use of geothermal energy are considered from the perspective of their relevance to the concept of the decarbonization of the economy efficiency, reliable, and continuous sources of energy. It presents Geotto, a comprehensive geothermal system that combines IoT, AI, and smart heat exchangers for agricultural and industrial demands. The project, already implemented in the pilot scale in the Eburu community of Kenya by using geothermal powered poultry incubation, proves the applicability of geothermal energy in crop drying, greenhouse control, and fish farming. Although this idea has attractive economic and environmental benefits, it has some technical and logistical problems such as policy limitation and lack of funds. This paper examines these challenges while portraying possibilities for future advancements, growth, and applicability in other areas of Kenya and even beyond. Through the analysis of Geotto's case, the paper emphasizes the importance of geothermal energy for the sustainable development and encourages other countries to replicate it in order to contribute to the process of decarbonization and stimulation of economic growth.

### Off-grid energy solutions for Agro-rural community development in Nigeria

*Nkolika O. Nwazor, Julius N. Aguni, and Remigius O. Okeke*

*Electrical/Electronic Engineering Department, University of Port Harcourt, Choba, Rivers State, Nigeria*

*Engineering Management Programme, University of Port Harcourt, Choba, Rivers State, Nigeria.*

*[nkolika.nwazor@uniport.edu.ng](mailto:nkolika.nwazor@uniport.edu.ng), [juliusaguni@gmail.com](mailto:juliusaguni@gmail.com), [remigius.okeke@uniport.edu.ng](mailto:remigius.okeke@uniport.edu.ng)*

**Keywords:** Off-grid Energy, Agro-Rural Community, Renewable Energy, Biomass Energy Hydro Energy, Solar Energy.

**Abstract:** Nigeria fondly regarded as the ‘Giant of Africa’ is the most populous country in Africa and the largest economy on the continent. However, despite the abundance of renewable energy means, Nigeria has been identified as a country with the largest energy access deficit in the world. This study therefore sought to elucidate various off-grid renewable energy opportunities that could be harnessed to engender rural electrification. The study specifically adopted exploratory research methodology to investigate the current state of the energy infrastructure of Agro-rural communities in Nigeria and identify off-grid energy solutions suitable for agro-rural communities and the potential impact of these solutions on community development and agricultural productivity. This study demonstrates that off-grid renewable energy solutions; solar, biomass, hydro and wind technologies are cost-effective alternatives to traditional energy sources that have the potential to significantly enhance agro-rural community development in Nigeria.

## **Design and Assessing the Effectiveness of Solar Disinfection Systems in Treating Rooftop Harvested Rainwater for Sanitation and Hygiene Purposes in Rural Maternal Health Facilities**

*Desire C. Mussa, Dr. Peter Binali Mbewe, Prof. Kevin G. McGuigan, and Prof. Christabel Yollandah Kambala*

1. *School of Engineering, Sustainable Energy (Mechanical and Electrical Engineering Departments), Malawi University of Business and Applied Sciences, 312200, Malawi*
2. *School of Engineering, Civil Engineering Department, Malawi University of Business and Applied Sciences, 312200, Malawi*
3. *Physiology and Medical Physics Department, Royal College of Surgeons in Ireland, University of Medicine and Health Sciences, DO2 YN77, Ireland*
4. *School of Science and Technology, Public and Environmental Health Department, Malawi University of Business and Applied Sciences, 312200, Malawi*

*mse21-dmussa@mubas.ac.mw/ desire.c.mussa@ieee.org, pmbewe@mubas.ac.mw, kmcguigan@rcsi.ie, ckambala@mubas.ac.mw*

**Keywords:** SODIS, Solar UV radiation, Total coliform, Escherichia coli, Water quality

**Abstract:** Malawi is one of the Sub-Saharan African countries with abundant solar energy resources. Solar energy has been used for electrification, water pumping, and domestic water heating in rural and urban communities. However, the productive use of solar energy for disinfecting water is not fully utilised despite being an eco-friendly solution to achieve the Sustainable Development Goals on clean water and sanitation. The productive use of sustainable energy has the potential to supplement Malawi’s government and the United Nations’ efforts to accelerate universal access to affordable and clean energy, water, and sanitation. The United Nations’ efforts to achieve the 2030 agenda on universal access to sustainable energy, clean water, and sanitation require affordable and environmentally friendly solutions that are socio-economically viable and easier to get. Several rural communities in the country do not have access to disinfected water. More than 85% of Malawi’s population stays in remote rural areas where the majority depend on untreated water that can compromise their health. This study aimed to enhance the conventional rooftop harvested rainwater Solar Disinfection (SODIS) method to be more effective and dependable for public health facilities in Malawi and other nations worldwide.

The study accomplished the 0 MPN/100 ml E. coli and 0 MPN/100 ml Total coliform water disinfection using solar UV radiation. Despite the focus on clean water for sanitation and hygiene in maternal health facilities, the study results achieved the water quality recommended by WHO's and MBS's drinking water standards.

## **Simulation and Experimental Performance Analysis of Portable Locally-made Solar-powered Cooler for Vaccine Storage**

*Vicent Marwa, Baraka Kichonge, Juma Rajabu Selemani, Thomas Kivevele*

- 1. School of Materials, Energy, Water, and Environmental Sciences, The Nelson Mandela African Institutional of Science and Technology, P. O. Box 447 Arusha, Tanzania.*
- 2. Department of Mechanical and Industrial Engineering, Mbeya University of Science and Technology, P.O. Box 131, Mbeya, Tanzania.*
- 3. Department of Mechanical Engineering Arusha Technical College, P. O. Box 296 Arusha, Tanzania.*  
*[kikohiv@nm-aist.ac.tz](mailto:kikohiv@nm-aist.ac.tz), [baraka.kichonge@nm-aist.ac.tz](mailto:baraka.kichonge@nm-aist.ac.tz), [juma.seleman@nm-aist.ac.tz](mailto:juma.seleman@nm-aist.ac.tz), [thomas.kivevele@nm-aist.ac.tz](mailto:thomas.kivevele@nm-aist.ac.tz)*

**Keywords:** poor vaccine storage, remote areas, optimum insulation, solar-powered cooler.

**Abstract:** Poor storage conditions, such as exposure to extreme temperatures, compromise vaccine efficacy, rendering them ineffective or harmful. This underscores the critical need for robust storage infrastructure and monitoring systems to ensure vaccine integrity, especially in remote areas with limited access to healthcare resources. This study analyzes the performance of a locally-made solar-powered cooler for vaccine storage in remote areas. Key findings include a reduction in temperature to  $-14.9^{\circ}\text{C}$  within 180 minutes, outperforming previous models. These results highlight the cooler's effectiveness in maintaining vaccine efficacy in resource-constrained environments. The study meticulously examined factors such as pressure within the cabinet, velocity flow, temperature distribution, optimum insulation thickness, and battery discharge rates through computational fluid dynamics (CFD) simulations and experiments. The experimental results, rigorously validated from the open literature, are reliable and accurate. The literature results reported that a minimum temperature of  $-10^{\circ}\text{C}$  was reached after 144 minutes compared to the current experimental results, which took 140 minutes at the same minimum cooling temperature. However, the experimental results reached a minimum cooling temperature of  $-14.9^{\circ}\text{C}$  after 180 minutes. Furthermore, the optimum insulation thickness was 0.07 m of cooling temperature  $-15^{\circ}\text{C}$  of polyurethane insulation material compared to 0.129 m of the Feather Fiber, equivalent to a 45.7% increase at  $42^{\circ}\text{C}$  ambient temperature. Similarly, for the ambient temperature of  $32^{\circ}\text{C}$  of the same cooling temperature, the polyurethane has the lowest thickness of 0.066 m compared to Feather Fiber, which has a thickness of 0.117, an increase of 43.6%. Meanwhile, modeling results give guidance for the experiments and comparison results successfully.

## **A Framework for Sizing Solar PV Systems Adaptable to Off Grid Areas**

*Nyangoka Isaac Kerina, and Vincent Omwenga*

- 1. School of Computing and Engineering Sciences, Strathmore University, Kenya*
- 2. School of Computing and Engineering Sciences, Strathmore University, Kenya*  
*[isaac.nyangoka@strathmore.edu](mailto:isaac.nyangoka@strathmore.edu), [vomwenga@strathmore.edu](mailto:vomwenga@strathmore.edu)*

**Keywords:** Solar Photovoltaic (PV), Sizing, Framework, Off grid

**Abstract.** Solar PV sizing is the process of determining the quantity and capacity of solar PV system components to meet a given energy demand. This process is needed to ensure that the components are not undersized resulting in insufficient energy or oversized increasing the system cost. There are several solar PV sizing frameworks currently in use in the market such as intuitive, numerical, and analytical frameworks. However, these frameworks have neglected some key adaptability factors unique to off-grid areas such as the ability of the household to pay, the roofing structure, and the ability of the system to be relocated. This neglect has seen development of solar PV systems that are beyond the budget of most households in off-grid areas and with specifications that technically inhibit their effective use in the off-grid setup. Therefore, for enhanced adaptability, there is need to develop a new solar PV sizing framework that considers the unique adaptability factors of off grid areas. This study identified these unique adaptability factors and investigated how they influence the size of a solar PV system. Through the modification of the existing numerical sizing framework, these adaptability factors were integrated in the sizing process within the context of this study. It was established that by integrating these factors, the resultant PV systems were more adaptable to off-grid areas in terms of cost, mobility, durability and reliability.

## **The Impact of Protective Devices on Photovoltaic (PV) System Performance and Installation**

*Praise Cyril Francis, Adesina Rukayat Olubunmi, Abubakarr Sall*

*1,2, 3. Electronics and Electrical Department, Obafemi Awolowo University, Ile Ife, Osun State, Nigeria.*

*cy4praise@gmail.com, adesinarukayat151476@gmail.com, sallabubakarr@gmail.com*

**Keywords:** Photovoltaic (PV) systems, Energy, Protective devices, Technical competency, Equipment, Safety, SPD, Circuit Breaker, Fuse, Overcurrent, Overvoltage, Short circuit

**Abstract:** The integration of photovoltaic systems into energy grids has been very common in recent times since more renewable forms of energy are sought after. Reliability and safety are among the most essential concerns that have to be considered for the deployment and operation of such systems. There have been some very conspicuous failures of protective devices in recent installations, leading to huge damage to solar equipment and an estimation of millions of Naira in repair and maintenance costs. The said incidents further underscore the need for technical competency in PV system installations as well as good-quality protective component acquisition. This paper reviews the role and effectiveness of protective devices in PV system installations. These include fuses, circuit breakers, and surge protection devices. All these are very important protective devices, which protect the PV systems against overcurrent, short circuits, lightning strikes, and ground faults. Using a case study, the paper discusses the financial implications of using substandard and damaged protective devices and policies that can be implemented to curb the challenge. The result of the case study shows that correctly selected and installed protection devices will save investors unnecessary maintenance and repair costs, bring personnel and equipment safety, and increase the life expectancy of the equipment. The paper also discusses standards and the best practices related to the sizing of these protective devices, emphasizing the necessity of following regulatory requirements and guidelines from NEC.

## Optical Characterisation of Dye Sensitized Solar Cells (DSSCs) Usin Natural Dyes Obtained From Leaves of Dacrodies Edulis, Mimosa Pudica, Delonyx Regia and Xanthosoma Saggittifolium

*Ujoatuonu, Amaka Love, Efurumibe, Ezinna Lucky and Asiegbu, Anyalewechi Daniel*

1. Department of Physics, Michael Okpara University of Agriculture, Umudike, Abia State, Nigeria.

2. Department of Physics, Michael Okpara University of Agriculture, Umudike, Abia State, Nigeria.

3. Department of Physics, Michael Okpara University of Agriculture, Umudike, Abia State, Nigeria.

[ujoatuonuamakalove607@gmail.com](mailto:ujoatuonuamakalove607@gmail.com), [efurumibe.ezinna@mouau.edu.ng](mailto:efurumibe.ezinna@mouau.edu.ng),  
[asiegbu.daniel@mouau.edu.ng](mailto:asiegbu.daniel@mouau.edu.ng)

**Keywords:** DSSC, Titanium dioxide, efficient sensitizers, Solar Cell Efficiency.

**Abstract:** Dye sensitized solar cells (DSSCs) using TiO<sub>2</sub> as a semiconductor material and natural dyes as sensitizer from dacryodes edulis, mimosa pudica, delonyx regia and xanthosoma saggittifolium leaves are successful produced. Photovoltaic parameters such as short circuit current density J<sub>sc</sub>, open circuit voltage Voc, fill factor FF, and overall conversion efficiency for the fabricated cells were determined under 100 mW/cm<sup>2</sup>. The results showed efficiencies of 0.01% (ff = 0.460, J<sub>sc</sub> = 0.62mA/cm<sup>2</sup> and Voc = 0.372V) for dacryodes edulis, = 0.05% (ff = 0.343, J<sub>sc</sub> = 0.05mA/cm<sup>2</sup> and Voc = 0.258V) for mimosa pudica, (ff = 0.586, J<sub>sc</sub> = 0.196mA/cm<sup>2</sup> and Voc = 0.483V) for delonyx regia and (ff = 0.348, J<sub>sc</sub> = 0.084mA/cm<sup>2</sup> and Voc = 0.385V) for xanthosoma saggittifolium. We have successfully showed that the DSSC using these four dyes as a dye sensitizer are useful for the preparation of environmental friendly and low-cost DSSCs.

## Assessing the Impact of Generator-Related Air Pollution on Stress Levels Among Printing Press Workers in Abuja, Nigeria: A Generalized Linear Model (GzLM) Analysis.

*Sammy Joel Panwal*

*Public Health Department, Faculty of Health Science, National Open University of Nigeria*

[sammyjoelpanwal@gmail.com](mailto:sammyjoelpanwal@gmail.com)

**Keywords:** Air Pollution PM<sub>2.5</sub>, PM<sub>10</sub>, Stress, Energy Poverty, Nigeria.

**Abstract:** The impact of air pollution on public and environmental remains huge burden in Nigeria that has not been properly addressed. Poverty energy supply has further exacerbated the current situations making business to rely on generators for energy power supply. This study aims to assess the impact of generators-induced air pollution on stress levels among printing press workers in a specific setting Abuja. This cross-sectional designed was adopted to conduct this study among printing press workers who use generators in Abuja. A total of 508 workers were selected using simple random sampling. Data on stress levels were collected using a validated perceive stress scale (PSS) 10 item scale, while exposure to air pollution from generators was assessed through on-site air quality monitoring device. A Generalized Linear Model (GLM) was employed to analyze the relationship between generator-related air pollution and stress levels, adjusting for potential confounders. Statistical analysis was performed using SPSS version 27, with significance set at  $p < 0.05$ . Results, shows that the mean PSS 10 scale was: >25.90 (SD 4.35), a bivariate correlation analysis indicates statistically significant positive correlation between the air pollutant variables and perceive stress,  $p$ -value 0.001.

A GzLM analysis show that; In model 1, the air pollutant variable was found to have a significant positive effect on stress scale (PM2.5:  $\beta = 1.029$  (95% CI: 1.024 -1.034)). In model 2, both the two air pollutants PM2.5 and PM10 were found to be significantly associated with increase in stress levels (PM2.5:  $\beta = 1.568$  (95% CI: 1.397 – 1.759)) and (PM10:  $\beta = 1.336$  (95% CI: 1.202 – 1.486)) separately. Contrary to model 1 and 2, most of the variables model 3 were not statistically significantly associated with increase in log odds higher perceive stress, except for PM2.5 which was adjusted. In conclusion, this study demonstrates statistically significant association between air pollutants and stress scale. The findings highlighted the importance of addressing energy policy issues and air quality concerns as potential factors affecting stress and mental health.

## **Modelling and optimization of hybrid photovoltaic-wind turbine with Energy storage system for autonomous electricity generation**

*C.P. Iwundu, E.O. Diemuodeke, J.C. Ofodu*

*Energy and Thermofluids Research Group, Department of Mechanical Engineering, Faculty of Engineering, University of Port Harcourt, PMB 5323, Choba, Port Harcourt, Nigeria*

*Corresponding author: iwunduchuks@gmail.com*

**Keywords:** renewable energy, hybrid energy system, optimization, african vulture optimization algorithm

**Abstract:** The integration of renewable energy sources, such as photovoltaic (PV) and wind turbines, has gained significant attention due to the growing demand for reliable and clean energy solutions. This paper presents a comprehensive modelling and optimization approach for hybrid PV and wind turbine systems to maximize system performance at the same time minimizing cost and surplus energy. The proposed model incorporates detailed mathematical formulations that capture the interactions between PV modules, wind turbines, and the storage system which is a battery energy storage system (BESS). The model also considers economic factors and methods to reduce the surplus energy of the system. The optimization scheme utilized the African vulture optimization algorithm (AVOA). The AVOA is a nature-inspired meta-heuristic algorithm created based on the hunting patterns of African vultures. In addition, the AVOA was constructed to handle a multi-objective optimization with size and costs as the objective functions. The optimized system provides the best system size to support the electricity supply of a coastline town (4.7231°N, 6.77881°E). The optimized system can deliver 41.80 GWh of energy annually, meeting 98.3% of the energy demands of the community; while the optimized system has a cost savings of 45.11%, with 92.9% penetration. The work provides valuable insights for system designers, energy planners, and policy-makers in their efforts to promote renewable energy integration and address the challenges associated with the transition to a low-carbon future.

## PART 7

### WASTE TO ENERGY

#### Energy Optimization Of Wireless Body Area Network(WBAN) Using TDMA Duty Cycling And Thermal Energy Harvesting

*Nkolika O. Nwazor, Justice C. Erowele, Remigius O. Okeke , Ekene S. Mbonu, & Otelemate M. Horsfall*

*1,2,3. Electrical/Electronic Engineering Department, University Of Port Harcourt*

*4. Mechatronics Department, Federal University Of Technology Owerri*

*[nkolika.nwazor@uniport.edu.ng](mailto:nkolika.nwazor@uniport.edu.ng) , [erowejustice@gmail.com](mailto:erowejustice@gmail.com), [remigius.okeke@uniport.edu.ng](mailto:remigius.okeke@uniport.edu.ng) ,  
[Ekene.Mbonu@futo.edu.ng](mailto:Ekene.Mbonu@futo.edu.ng) [otelemate.horsfall@uniport.edu.ng](mailto:otelemate.horsfall@uniport.edu.ng)*

**Keywords:** Wireless Body Area Network (WBAN), Energy Harvesting, TDMA, Duty Cycling, Energy Harvesting, Thermoelectric Harvesting

**Abstract:** Energy Harvesting Is An Effective Technique For Optimizing Wireless Body Area Network (WBAN) Devices Used In The Delivery Of Continuous Healthcare Services To Patients. Constraints In Power Associated With WBAN As A Result Of Storage Limitations Have Prompted The Study Into Means Of Scavenging, Harvesting And Utilizing Available Energy Sources. In This Paper, Energy Optimization Of WBAN Using TDMA Duty Cycling And Thermal Energy Harvesting Is Proposed. The Proposed Model Aims To Enhance Energy Efficiency In A Wireless Body Area Network (WBAN) By Using Time Division Multiple Access (TDMA) And Thermoelectric Harvesting (TEH) Techniques. At The Heart Of This Model Is An IoT Controller Which Runs On A Single-Sensor Activation Principle At All Times, Controls The Sensor Function And Stores The Sensor Data In Its Internal Memory (Buffer), Enabling Efficient Data Management And Transfer, Guaranteeing That Just One Sensor Is Turned On When Data From That Sensor Is Required. Implementing The TDMA Duty Cycle Guarantees That Sensor Nodes Are Enabled And Powered Only When Necessary, Reducing Idle Time And Saving Energy. The TDMA Scheduling Ensures That Multiple Sensors Are Engaged In A Coordinated Manner, Reducing Network Collisions And Contention, Hence Contributing To Energy Savings Which Is Critical To Our Energy Optimization Plan. The Proposed Optimization Model Shows A 52.40% Improvement In The Energy Conversation Of The WBAN Device, Thus Increasing The Battery's Useful Life By More Than 50%.

#### Status Clay-based Microbial Fuel Cell System in BOD from Petroleum Contaminated Wastewater and Energy Generation

*Kabo Benedict Jongman, Dr Girum Ayalneh and Dr Getachew Dagnew*

*Addis Ababa, Addis Ababa University , Ethiopia*

*[jongmanbenedict@gmail.com](mailto:jongmanbenedict@gmail.com), [girum.ayalneh@aau.edu.et](mailto:girum.ayalneh@aau.edu.et), [getachew.dagnew@aau.edu.et](mailto:getachew.dagnew@aau.edu.et)*

**Keywords:** Biological Oxygen Demand, Clay-based membrane, Microbial Fuel Cell, Petroleum Wastewater

**Abstract:** This study explores the application of a clay-based microbial fuel cell (MFC) system for the treatment of biochemical oxygen demand (BOD) in petroleum-contaminated wastewater. The petroleum industry is the backbone of most industries ranging from construction and energy fields.

This leads to a pollution of water resources either from transportation, refinery and usage of petroleum products. Eventhough petroleum is crucial in our day to day activities, the complex substance it contains have dire implications on the ecological stability. These pollutants compromise both the aquatic fauna and Fiona. Therefore this paper is about a study throughwhich a clay microbial fuel cell was used to removed BOD in petroleum contaminated wastewater and generate green energy. Three clay microbial fuel cells were assembled and ran at batch mode for 30 days.MFCa and MFCb were fed with a culture of micro organisms from filling station waste and MFC c had no inoculation of the microbes.A maximum removal efficiency of 91% and 89% was achieved from MFCs with microbes and only 30% from the control with no inoculation (MFCc) .A maximum of 250mV of open circuit voltage was generated from the treatment of the petroleum wastewater using the clay microbial fuel cell.

## **Comparison of energy recovery from organic waste from human body and primary sludge**

*Xumay Bura Hhaygwawu, Achisa C. Mecha and Jacqueline K. Makatiani*

1. Department of Mechanical Production and Energy Engineering, Moi University, P. O. Box 3900 – 30100 Eldoret, Kenya.

*E-Mail: buraxumay@yahoo.com/engdes0819@students.mu.ac.ke*

2. Department of Chemical and Process Engineering, Moi University, P. O. Box 3900 – 30100 Eldoret, Kenya. *E-Mail: achisacm@mu.ac.ke*

3. Depatment of Biological Science, Moi University, P. O. Box 3900 – 30100 Eldoret, Kenya.

*E-Mail: jkmakatiani@mu.ac.ke*

2. Rural Water Supply and Sanitation Agency (RUWASA), Ministry of Water, P.O. Box 142, 40473 Dodoma, Tanzania.

**Keywords:** Energy Recovery, Organic Waste from Human Body, Primary Sludge. Biogas.

**Abstract:** Increases in demand for energy have caused some waste treatment facilities to be converted to energy recovery including municipal wastewater treatment plants (MWWTPs). This study was conducted to evaluate the comparison of biogas production between organic waste from the human body (OWHB) and primary sludge (PS) from the treatment plant. The average biogas production was 1.85M3/ca.year for OWHB and 0.013M3/ca.year for PS. It can be concluded that OWHB is the best substrate for energy production compared to PS. Its production is directly proportional to the increase in human population.

## **Valorization of Mixed Blackwater/Agricultural Wastes for Bioelectricity and Biohydrogen Production: A Microbial Treatment Pathway**

*G. Plason Z. Plakara, Emeka Emmanuel Oguzie, Abdulsalami S. Kovo, Kanayo L. Oguzie*

1. African Centre of Excellence in Future Energies and Electrochemical Systems (ACE-FUELS), Federal University of Technology, Owerri, PMB 1526, Imo State, Nigeria.

2. Federal University of Technology Owerri, Imo State, Nigeria

3. Department of Chemistry, Emmet A. Dennis College of Natural Sciences, Cuttington University, Republic of Liberia

4. Federal University of Technology Mina, Nigeria

[plakar.plasonz@gmail.com](mailto:plakar.plasonz@gmail.com), [emeka.oguzie@futo.edu.ng](mailto:emeka.oguzie@futo.edu.ng), [kovo@futminnaedu.ng](mailto:kovo@futminnaedu.ng),  
[kanayo.oguzie@futo.edu.ng](mailto:kanayo.oguzie@futo.edu.ng)

**Keywords:** Blackwater, agricultural waste, Microbial treatment, Bioelectricity, Biohydrogen.

**Abstract:** The objective of this study was to evaluate the possibility of co-treating blackwater and agricultural wastes while co-producing bioelectricity and biohydrogen using a microbial treatment path using a dual chamber MFC and to determine the optimal feedstock ratio and pH conditions. An integrated MFC was designed to achieve this goal. The main microorganisms present included *Escherichia Coli*, *Salmonella* spp., *Pseudomonas aerogunisa*, *Shigella* sp., *Klebsiella pneumonia*, *Enterobacter asburiae*, *candida guillermundii*, and *Pythium ultimum*. The highest open circuit voltage generated was 1090 mV from MFC-4 at HRT=6 days. The maximum COD and BOD removal efficiencies were 90.87% and 76.67%, respectively, with a Columbic efficiency of 40.17%. The maximum power density was 345 mW/m<sup>2</sup>. The highest H<sub>2</sub> yield was 483 ppm/s. The optimal feedstock ratio was cassava peel (300 g): banana peel (100 g): Tomato waste (100 g) or 3:1: 1. The optimum conditions for pH were basic medium (pH 9.35). This study highlights the potential for bioelectricity and biohydrogen production from the microbial treatment of mixed blackwater / agricultural waste in one system without the need for chemical pretreatment.

## **Biowaste To Bioenergy For Sustainable Energy Supply And Industrial Development In Nigeria: A Review Of Opportunities And Challenges.**

*Nmachukwu Onyema*

*Integrated Africa Power (IAP), [Nmachukwuonyema@Gmail.Com](mailto:Nmachukwuonyema@Gmail.Com)*

*Chigozie Nweke-Eze*

*Integrated Africa Power (IAP), [Cne@Intafripower.De](mailto:Cne@Intafripower.De)*

**Keywords:** Bioenergy, Biowaste, Sustainable Energy, Industrial Development

**Abstract:** The Current Industrial Crisis In Nigeria Stems From The Worsening Energy Situation – A Growing Concern Evidenced By The Recent Shutdown Of Some Industrial Companies Within The Country. This Crisis Arises Due To High Cost Of Energy Consumption, Which In Turn Inflates The Cost Of Local Production And Drastically Minimizes Profit. Despite Nigeria's Significant Oil And Gas Production Levels, Energy Sector Challenges Impede Economic Progress. Nigeria Faces A Shortage In Electricity Generation Capacity, Heavily Relying On Unsustainable Options Like Diesel-Powered Generators. These Conditions Highlight The Urgent Need For Sustainable Energy Sources To Address The Energy Crisis Effectively. Additionally, Nigeria Grapples With Mounting Agricultural Bio-Waste From Rural And Commercial Sectors. This Paper Explores The Potentials And Challenges Of Biowaste To Bioenergy (BtB) In Sustainable Energy Supply And Industrial Development In Nigeria. We Argue That Converting Bio-Waste To Bioenergy (BtB) Presents Substantial Opportunities To Combat Energy Challenges In The Country. Furthermore, Incorporating Renewable Energy Promotes Business Growth, Economic Development, And Job Creation While Combating Climate Change Effects.



[www.toveroenergy.com/aiccees](http://www.toveroenergy.com/aiccees)